



MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT NAME: SAFEGUARD 30
PRODUCT USE: For use as a roofing underlayment
3144 SE Tualatin Valley Hwy, Hillsboro, OR, 97123
www.safeguard30.com – info@safeguard30.com – (503)-906-0768

SECTION 2: COMPOSITION INFORMATION ON INGREDIENTS

36.5% Asphalt Compound, 34.1% FG/Synthetic scrim, 29.4% Other materials / Synthetic fabrics

SECTION 3: HAZARDS IDENTIFICATION

This is not a hazardous product as defined by WHMIS

SECTION 4: FIRST AID MEASURES

N/A

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABILITY: Not flammable, but in case of fire, will contribute.

FLAMMABLE LIMITS IN AIR, UPPER: N/A
(% BY VOLUME) LOWER: N/A

FLASH POINT: N/A

METHOD USED: N/A

EXTINGUISHING MEDIA: Water spray and dry chemicals.

EXPLOSION HAZARDS: Not sensitive to impact or static discharge.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides

SECTION 6: HANDLING AND STORAGE

HANDLING AND STORAGE: Rolls should be properly restrained to prevent shifting during handling and storage

SECTION 7: PREVENTIVE MEASURES

LEAK AND SPILL PROCEDURE: N/A

RESPIRATORY PROTECTION: No respirator required under normal use

EYE PROTECTION: N/A

PROTECTIVE CLOTHING OR EQUIPMENT: N/A

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Black Woven Fabric.

ODOR: Minimal asphalt odor

PHYSICAL STATE: Solid

pH: N/A